



 9001 E	 9002 E	 9006 E	 9006 E Stainless	 9500 E
Number of doors/compartments	1	2	6	6	1
Max. number key hooks/spaces	29	16	-	-	216
Max. number users/codes	-	-	-	-	-
Max. number accesses	-	-	-	-	-
Can be connected to alarm	-	-	-	-	-
Can be connected to card reader	-	-	-	-	-
Battery backup	-	-	-	-	-
Display, number of rows/ characters	-	-	-	-	-
Memory	-	-	-	-	-
Clock	-	-	-	-	-
Time zones	-	-	-	-	-
Setting blocking function	-	-	-	-	-
Setting magnetic time for compartment	-	-	-	-	-
Double code	-	-	-	-	-
Can be connected to KeyWin S	-	-	-	-	-
Requires KeyWin SC	-	-	-	-	-
Max. number of expansion cabinets	-	-	-	-	-
Expandable using multiple main cabinets	-	-	-	-	-
Exterior dimensions	345x280x94	345x280x94	345x280x94	345x280x94	746x730x140
Weight	4,3 kg	4,3 kg	4,3 kg	4,3 kg	27 kg
Voltage, 230V / 50HZ	-	-	-	-	-
Power consumption, max. 35 W / 0.15A	-	-	-	-	-
Power consumption, max 65W / 0.3A	-	-	-	-	-
Control unit, microprocessor	-	-	-	-	-
Memory for codes	-	-	-	-	-
Lock, electromagnetic 12V	YES	YES	YES	YES	YES
Cabinet material, steel	1,5 mm	1,5 mm	1,5 mm	1,5 mm	1,5 mm
Exterior finish, brushed stainless steel	-	-	-	YES	-
Exterior finish, weather resistant powder coating	YES	YES	YES	-	YES
	-	-		-	-
	-	-		-	-
	-	-		-	-